

## **AUTOMATIC**



HOOD FANS

18" - 24" - 36"

A <u>NEW</u>
GENERATION
OF FANS

**QUALITY BUILT.** 

## PRICED RIGHT. NEW CONVENIENCES! LONG LIFE!

- THREE SIZES: 18 inch. 24 inch. 36 inch.
- MOUNTING: Interior flush mounted. Installed quickly and easily. Extends only 10 inches on the outside of the building (average wall) when not operating.
- SAFETY SCREEN: Easy slip-out design. Easily cleaned. Heavy gauge galvanized wire.
- **SHROUD:** Deep throat for efficient air movement. Heavy gauge galvanized, spun steel construction.
- FAN BLADE: Polished cast aluminum.
   Stays cleaner and moves more air. <sup>⋆</sup>
  - \*36" fan has extruded aluminum blade.

- MOTOR: Efficient single speed 230V. Totally enclosed ball bearings. Thermal protected.
- MOTOR MOUNT: Rugged construction. Easily removed,
- WIRING: Equipped with three wire cord and junction box.
- HARDWARE: Zinc plated throughout.
   All bolts have self-locking nuts. All hardware is furnished.
- LONG LIFE

All welded construction, weather-proof metals and acrylic plastic exterior hood and less parts all combine to assure long life.

## **CHORE-TIME AIR SYSTEM FAN CONTROLS**




Modulator
Controls one or two
fans

Single Stage
Thermostat
Controls temperature



Time Clock
Assures periodic fan
operation on a 10
minute repeating
cycle.

Single Stage
Thermostate Panel
Controls one single





Time Clock and Single Stage Thermostat Panel Time clock controls the fan on a ten-minute repeating cycle or thermostat will oper-

ate the fan as needed.

## DON'S SALES & SERVICE

241 WEST MAIN STREET

PHONE 354-9745

NEW HOLLAND, PENNA.