

The Series 2100 posthole quire six inch to 24 inch malleable steel heads in six, digger from Bush Hog is designed for one-man operation to speed fence installation, tree planting, construction and other jobs that re-

holes. Augers feature replaceable, forged harden-

replaceable

nine, 12, 15, 18 and 24 inch diameters and 48 inch ed alloy steel cutters and pearlitic

CONTROL WEEDS IN ALFALFA WITH **BUTYRAC-200**

Apply 2 to 4 weeks after alfalfa emerges. Controls broadleaf weeds in seedling or established legumes. This remarkable selective action - killing many broadleaf weeds without affecting certain broadleaf crops - has been proven by research men and commercial growers throughout the country.

We are distributors for a complete line of

WEED KILLERS P. L. ROHRER & BRO., INC. Smoketown, PA Ph: 717-299-2571

lengths. Single-flight augers are available in six through 12 inch diameters with continuous-weld helical flighting. Double flight augers have ¹/₄-inch-thick sectional flighting and are available in 15 to 24 inch diameters.

The heavy-duty boom is constructed of 3½-inch diameter tubing with a reinforcing rib and welded steel fittings.

The gearbox features machined, hardened gears, one-piece, two inch diameter output shaft mounted in two tapered roller bearings and a three-year warranty The drive shaft comes with standard safety shields.



Holz Kwik-Lag Kwik-Lag Reduces Belt Slippage on

Small Diameter Pulleys Kwik-Lag, a lagging for small diameter conveyor and elevator pulleys, is now available from Holz Rubber Company, Loái, Calif. It is ideally suited for package handling, food processing, agriculture, lumber and wood processing and light industrial or bulk material applications. Kwik-Lag is designed to give superior driving traction and reduce belt slippage when com-pared to other lagging methods. This means consistent, trouble-free load handling and substantially

increased lagging life. Kwik-Lag is made from a quality elastomer which may be varied for special service conditions. The elastomer is hot vulcanized to a rust-resistant steel backing plate to give the pad extra durability. The lagging pads feature double herringbone grooving for non-slip action even in wet conditions. Self-drilling/selftapping fasteners are provided, but alternate. fastening such as pop riveting may be used to attach the lagging to the pulley. Installation and replacement normally may



Sealant tape stops leaks

CLEVELAND - Revere Chemical Corporation's new aluminum backed sealant tape, Luma-Seal, stops leaks and drafts instantly. Extended service life is due to the protective layer of aluminum foil which reflects the destructive ultra-violet rays of the sun, and is in itself, an additional waterproofing layer to the mastic.

Applied by hand pressure, it sticks to any clean, dry surface, and the longer it stays, the tighter it sticks for permanent repairs. LumaSeal provides an instant weathertight seal for fixing all types of flashing and roof leaks.

In addition, it is ideal for sealing cracks, gaps, and is particularly suited for metal related applications because of its highly reflective finish. Uses include gutters and downspouts, glaze bars and roof lights in greenhouses, leaks in truck cabs and trailers, seams in airconditioning ducts, around rooftop units, vents, awnings, metal outbuildings and utility sheds, and more.



Applied by hand pressure, sealant tape molds itself to many surfaces for repairs.

be completed without removing belting or pulleys from the system.

Designed for use on pulleys with diameters as small as 2", Kwik-Lag is available in 48" lengths that may be cut to fit virtually all

pulley face widths. Kwik-Lag is a registered trademark with patent pending. For further information, contact Holz Rubber Company, 1129 S. Sacramento St., P.O. Box 108, Lodi, CA 95240.

Feeder mixer announced

DODGE CITY, Ks. - B.J. Manufacturing Co., Inc., announces the introduction of the new model 2912 mixer feeder.

An intermediate model designed for the farmerfeeder and dairyman, the 2912 has a mixing capacity of 280 cubic feet. The 2912 has a low profile to facilitate loading, the basic three auger mixing system, and a clean, stylized design.

Standard equipment on the BJM 2912 includes a twin auger 40" wide discharge conveyor, ¼" high strength bottom, a hydraulically operated discharge door and conveyor spout, an enclosed oil bath drive, and a three point electronic scale

We're bringing banking closer to you with...



Banking Centers.

system.

III

It's estimated there are more than 163,000 supermarkets, small grocery stores and convenience food stores in the U.S.

FOR SALE

Air Dried PA White **Pine & Hemlock** Lumber. Sheeting & framing, rough or planned on 4 sides. All 2" framing finished at 134 thickness.

— Also — Hardwood planking & beam timbers

LEBO'S SAWMILL RD 1, Tower City, PA 17930 717-647-9667 & 647-2482 after 4:30 P.M.