



KEYSTONE AG ASSOCIATES, INC.

Manufacturers Representatives of Products & Services For The Agri Industry

PA. FARM SHOW, Dairy Barn Spaces 8 & 9

FEED TANKS

Victoria

AUGERS

GRAIN BINS

HOPPER TANKS

12'-0" (3,66m) ▶ 45° & 60°
 15'-0" (4,6m) ▶ 45°
 5" (13 cm) Corrugation

GRAIN MOISTURE TESTER
Test Hay Or Silage Moisture
With The Optional Hay Probe Attachment.

Take the guesswork out of haying with the new FARM I hay probe attachment. For loose hay or silage simply push the probe into a bucket filled with a sample and note the moisture reading. Then use the handy slide rule to convert the meter reading into moisture content (Measures silage up to 70%). For baled hay follow the same procedure except push the probe into the hay bale itself. Repeat the test a couple of times to get the average of the whole lot.

FARM I

3 Portable Temperature Meter: To take a reading, the meter is plugged into one extension cable at a time. Simply push the button and read the temperature instantly off the dial! Use the same portable meter on all bins.

TEMP-TEST

Simple Installation — Easy Operation The FARM I TEMP-TEST consists of the following parts:

- Sensor-Probes:** The Sensor-Probe is 5 feet long and contains one heat-sensor at the tip. It can be easily pushed into the grain or removed for stirring or sweep augering. Two or more Sensor-Probes may be positioned in the same bin, in different locations.
- Extension Cables:** Each Sensor-Probe comes with attached extension cable. The cables are available in 6 different lengths to fit all bin sizes.

RILEY
Bucket Elevators

Riley standard bucket elevators are available in capacities ranging from 900 to 10,000 BPH. The Riley Galaxy Series bucket elevator is available in capacity range of 10,000 to 30,000 BPH. All are top-quality elevators built tough for a long service life.

VINYL DROPPING BOARDS

RILEY CONVEYORS

The Riley Easy-Flo Drag Conveyor is designed with #10 ga galvanized bolted sides and bottom as standard construction. Other mild steel thicknesses and AR plate are optional for bottom or sides. Bolted cover is constructed with #14 ga galvanized steel. Models are available in sizes ranging in capacities from 3,000 to 30,000 BPH. Special heavy duty welded chain and hardened rim sprockets with 1/2" UHMW flights are Riley features. A complete line of accessories is available for each model.



Keystone Ag Associates, Inc.
 RD 6, Box 456
 Manheim, PA 17545
(717) 569-6428

For name and address of your nearest dealer/distributor -- Clip & Mail
 To: KEYSTONE AG ASSOCIATES, INC. - RD #6 - Box 456 - Manheim, Pa 17545

Name _____
 Address _____
 City _____ State _____ Zip Code _____
 Phone with Area Code _____

Grain Bins
 Hopper Bins
 Feed Bins
 Augers
 Moisture Testers
 Bucket Elevators
 Drag Conveyors
 Dropping Boards