VAN DALE

K & SINC.

Invites You To See Us

PA FARM SH

January 11-16 Space #21-23, 40-42

THE LAGOON PUMP... All New From Van Dale

On Display

Fully Hydraulic Controls With Up To 6,000 Gal. Per Minute Capacity -SPECIFICATIONS-

Maximum width (wheel to wheel) 8' wall thickness Shaft Single piece, 1¾" diameter PTO..... 540 RPM; 125 HP shaft

bearing Intermediate bearing.....(2) 21/4" tapered roller

bearings

Full tube support is tractor mounted; transport locking bar; 100 HP suggested for maximum performance.

The All <u>New</u> Total Mixed Rations With The <u>New</u>

On Display

Designed and Manufactured by Van Dale

- NEW DRIVE Simple, more efficient, Lower Horsepower Requirements (eliminates large troublesome drive chain
- Internal Adjustable U-Trough Mixing/Discharge System.
- Two Barrel Designs: H.D. Painted Mild Steel or Stainless Steel.
- Simple Exterior Control of Discharge.
- Higher Discharge Location.
- Smooth Spun Drum End.
- Scale Bar located under unit, out of the way for better operation.
- Larger more aggressive Mixing Ribs for faster, more complete
- New quiet Front Support Rollers w/Bearings.
- Increased Mixing Capacities with new Barrel angle.



FEATURING



UEBLER FEED MACHINES

- ☐ THE ALL NEW UEBLER 808 HYDROSTATIC **WALK-BEHIND CART** AT GREATER **SAVINGS!**
- ☐ THE U-BLEND™ GAS OR ELECTRIC **POWERED TMR FEED** CART DESIGNED FOR STALL BARNS
- THE UEBLER GAS **POWERED SILAGE** CARTS, MODELS 808, 810 OR 812
- □ UEBLER WATER BOWLS



Features No One Else Can Claim: Tested in Northwestern States Under Severe Freezing C

 Ring Drive That Hangs On A Single Suspension Without The Old Clumsy Type Ring

You Do Not Need A 3-Cable Design, No Spending Extra Money For Special Tri-Pod Or Hexa-Pod



Under Severe Freezing Conditions

The Magna-Matic 360's Performance Is Extraordinary

- Positive drive in loose and frozen material
- Smoother operation i extremely tough conditions
- The silo can be filled to the top, increasing silo capacity by several tons Quicker changeovers from fill to feed and back
- to filling Can utilize existing single cable suspension with sufficient weight
- carrying specifications The surface of the silage or grain is not disturbed
- by a drive wheel Steadier delivery of silage with less frequent winch adjustment
- Less installation time than conventional ring

K & S INC. Sales & Service R1, Quarryville, PA