

WCA1 Carry-All: An All-Purpose Tool, One Of The Strongest On The Market. Can Be Floored. A Great Help In Moving Heavy, Bulky Items With Ease.



• 3 Pt. 5 1/2' Disc, 18" Blades - \$625

• 3 Pt. 6 1/2' Disc 18" Blades - \$675

• 3 Pt. Heavy Duty 8' Blade - \$650

May Be Put On Credit Card.

• 3 Pt. Fertilizer Spreaders - 600 Lb. Capacity - \$395


• 3 Pt. 2 Bottom Plow \$340

• 3 Pt. Carry All-\$95

• 3 Pt. 1 Bottom Plow \$225

• 3 Pt. 4 Wheel Rake - \$530

In The Market For A Good Mower Conditioner? See Us For A Demonstration!



Thoroughly Conditioned
Several 9'3" Cut Model 2170 IN STOCK!

The Gehl 2140/2170 mower conditioner will thoroughly condition your hay. These pull-type mower conditioners are built for fast cutting, fast drying and worry-free performance. The wide, intermeshing rubber rolls with intermittent ribs give you 35% more working edges than continuous-ribbed rolls, for more thorough conditioning. That means shorter drying time with less leaf damage. See Binkley & Hurst, your Gehl dealer today on how the 2170 with a 9 ft 3 in cutting width, will fit into your haymaking operation. 3 Pt Suspension!

The Super Mower -
See Us For A Demonstration!



109 Inches of Quality Conditioning

A Gehl center-pivot, swing frame mower conditioner gives you high capacity cutting and conditioning with outstanding maneuverability. Two models are available, the 2240 with 12'3" cutting width and the 2270 with 14'3" cutting width. Both models feature wide 109-inch rubber conditioning rolls with intermittent tread design to deliver thorough, uniform conditioning. These machines pivot at the center of the frame for easy header positioning, reducing cutting time and lowering fuel costs. And total hydraulic drive means smooth operation and low maintenance. Put a Gehl swing frame mower conditioner to work for you today!

Model 2240 In Stock At 12'3"
Cutting Width - Priced Right!

Ask For Landis

ATHENS MODEL 200
HEAVY DUTY PLOWING DISK
(Also Levels) With Double Offset Design & Heavy Duty Rockflex Spring Bearing Hangers With 11'10" Cutting Width

NEW - The Quality Is Good: Come & See!



With 10" Blade Spacing And 24" Diameter x 1/2" Blades - 6000 Lbs.

Set UP & Ready To Work!

No. 6925 List Price Over \$10,572
SPECIAL OFFER ONLY \$7,995 Ask For Amos Sr.



RTS ROTARY TILLER FEATURES:
• Offset capability w/driveline in line w/tractor
• Solid rotors • Tough #80 chain drive
• High carbon, long-life steel blades
• 10 gauge high strength steel deck construction

Bush Hog 3 Pt. Rota Tillers
Bush Hog Tiller 38" 3 Pt. w/24 Blades, Chain Drive.....\$1,155
Bush Hog Tiller 50" 3 Pt. w/36 Blades, Chain Drive.....\$1,390
Bush Hog 62" 3 Pt. w/40 Blades, Chain Drive.....\$1,475
Model 3126-02 10 1/4' Pull Model Rotary Mower w/Hyd. Lift.....\$4,650
Model 3108-02 9' Pull Mower w/Hyd. Lift.....\$4,250
Model 2615 15' Batwing Mower w/Hyd. Wing & Lift, Used Tires.....\$7,875
Model 2615-03 15' Batwing Mower w/Hyd. Wing & Lift, w/6 Solid Tires.....\$8,400

Closed Ascension Day - Thursday, May 9th

BINKLEY & HURST BROS. INC. (717) 626-4705

133 Rothville Station Rd. • Lititz, PA 17543
Located 1/4 Mile North Of Rothville

SALES
— SERVICE —
PARTS

New Athens 3 Pt. High Clearance Spring Shank Chisel Plows IN STOCK!

- 2 Bar, 8 Shank
- 3 Bar, 7 Shank

Come In For A Quality Chisel Plow Now!

RICHARDTON


MODEL 750 MULTI-PURPOSE DUMP WAGON

The Model 750 dump wagon features a 1000 cubic foot capacity box, low center of gravity, high dumping clearance and a rugged frame.

The diagonal slide and dump system allows easy access to the center of your truck.

30,000 lb. lift capacity

SAVE: Labor • Time • Equipment



Get a step ahead at harvest with fast, reliable Richardton Dump Wagons that handle big loads under all field conditions.

More sizes, more options, more strength, more uses, and less maintenance - that's what makes Richardton wagons so popular with silage, haylage, corn, vegetable and grain growers.

Additional features include:

- One valve hydraulics to operate the lift, stabilizer and lock cylinders
- Offset hitch to allow for different row crop spacings

- Galvanized roof with expanded metal insert for straight through air flow and mechanical positive action roof opener

Harvest A Variety Of Crops

- Silage • Haylage
- Chaff • Straw • Tomatoes
- Cucumbers • Sweet Corn
- Seed Corn • Ear Corn
- Peas • Beans • Carrots
- Sugar Beets • Grain

Model 750 Specifications:

Capacity	Hydraulic System
Capacity With Roof 1000 cu ft	Stabilizer Cylinders 2 5" x 4"
Capacity Without Roof 750 cu ft	Lift Cylinders 4 5" x 7 8"
Rated Load Capacity 30 000 lbs	Lock Cylinders 2 5" x 3 0"
Shipping Weight 8 400 lbs	Recommended Hyd. Fluid Flow 8 GPM
Dumping Angle 45	Recommended Pressure (Min) 1800 PSI
Standard Tire Size 16 5 x 22 5	Recommended Pressure (Max) 2200 PSI
Wheel (8 hole) 12" x 22 5"	Volume Required To Charge 9 0 Gal
Length (box only) 15	Volume Required To Operate 4 0 Gal
	Minimum Reservoir Capacity 11 5 Gal
	Dump Cycle (3) 2 Min
Dimensions	
Dumping Clearance (1)(2) 11	
Unassembled Height 8 7"	
Lip Clearance 14"	
Ground Clearance 15"	
Loading Height (2) 10	
Standard Wheel Width 109"	
Height With Forage Roof 13	
Forage Roof Height 30"	

(1) Optional risers available to provide additional 6" dumping clearance
(2) Loading height and dumping clearance will vary slightly depending on tire size and tread wear
(3) Dump cycle time depends on hydraulic supply output
Richardton Manufacturing Company reserves the right to improve or modify its product without notice or obligation

Model 700 Specifications:

Capacity	Auto-Steer	Tandem	Hydraulic System	Auto-Steer	Tandem
Capacity With Roof 750 cu ft	750 cu ft	750 cu ft	Stabilizer Cylinders 2 5" x 4"	2 5" x 4"	
Capacity Without Roof 550 cu ft	550 cu ft	550 cu ft	Lift Cylinders 4" x 7 8"	4" x 7 8"	4" x 7 8"
Rated Load Capacity 20 000 lbs	20 000 lbs	20 000 lbs	Lock Cylinders 2 5" x 3 0"	2 5" x 3 0"	2 5" x 3 0"
Shipping Weight 6 200 lbs	7 200 lbs	7 200 lbs	Recommended Hyd. Fluid Flow 8 GPM	8 GPM	8 GPM
Dumping Angle 45	45	45	Recommended Pressure (Min) 1800 PSI	1800 PSI	1800 PSI
Standard Tire Size 11 00 x 20	11 00 x 20	11 00 x 20	Recommended Pressure (Max) 2200 PSI	2200 PSI	2200 PSI
Wheel (8 hole) 8" x 20"	8" x 20"	8" x 20"	Volume Required To Charge 6 4 Gal	6 4 Gal	6 4 Gal
Length (box only) 12	12	12	Volume Required To Operate 3 9 Gal	3 9 Gal	3 9 Gal
			Minimum Reservoir Capacity 8 3 Gal	8 3 Gal	8 3 Gal
			Dump Cycle (4) 2 Min	2 Min	2 Min
Dimensions	Auto-Steer	Tandem			
Dumping Clearance (1)(2) 10 9"	10 9"	10 9"			
Unassembled Height 8 9"	8 9"	8 9"			
Lip Clearance 18 3 4"	19 1 4"	19 1 4"			
Ground Clearance 15"	15"	15"			
Loading Height (2) 9 10"	9 10"	9 10"			
Standard Wheel Width (3) 109"	109"	109"			
Height With Forage Roof 12 9 1 2"	12 9 1 2"	12 9 1 2"			
Forage Roof Height 30"	30"	30"			

(1) Optional risers available to provide additional 6" dumping clearance
(2) Loading height and dumping clearance will vary slightly depending on tire size and tread wear
(3) 109" optional for auto steer
(4) Dump cycle time depends on hydraulic supply output
Richardton Manufacturing Company reserves the right to improve or modify its product without notice or obligation

When Your Truck Reaches The Blower, Just Back Into Your **RICHARDTON** Conveyor Box, Dump Your Load And Race Away For The Next!



BINKLEY & HURST BROS. INC.

133 Rothville Station Rd.
Lititz, PA 17543
Located 1/4 Mile North of Rothville
(717) 626-4705

Machinery Sales Hours:
Mon.-Fri 7 AM - 5 PM;
Sat 7 AM - 11:30 AM
Sun Closed - Lord's Day

AFTER HOURS:
EMERGENCY PARTS CALL
(717) 626-0885 (717) 626-5159
(717) 859-8768

New Parts Dept. Hours
Mon., Tues., Thurs., Fri.
7 AM - 8 PM
Wed. 7 AM - 5 PM
Sat. 7 AM - 12 NOON