



FARMER BOY AG INC.



Your Complete Poultry & Swine Building & Equipment Center

SOW MATS

Ribbed rubber sow mats for covering those problem floors. Especially good for covering 5 gauge wire where nipple problems and shoulder sores are a problem.

24 x 40 UPS Weight 41 lbs
24 x 72 UPS Weight 49 lbs

Extra Long Wear
Superior compounding and approximately 3/4" thickness provide added insurance against wear, aging and loss of service.

Secure Footing
Special soft rubber compound provides elastic cushion for less leg fatigue. "Sure grip" textured surface gives solid footing, protecting against injuries.

Improved Health
3/4" high density rubber provides insulation from cold and dampness for healthier, happier sows.

Grooveless Surface Cleans Easily
Ribbed surface has no groove to retain urine or manure. Washes easily. Dries quickly with minimum effort.

Elasticity	Indentation depth 3/16" at an impact of 440 lbs
Weight	4 lbs per sq ft
Thickness	Approximately 3/4"
Color	Black
Sizes	15' x 40' 48' x 72' 48' x 60' 54' x 72'

BOAR MATS

AGRI-MAT reduces the onset of fatigue and strain and pays for itself in a short time. Afterwards, all savings are all profit.

Agri-Mat is a scientifically developed and tested mat that cuts cleanup time and provides improved sanitation.

Reduces Fatigue
Our advanced rubber chemistry and design groups have developed a semi elastic body that supports the working man with just enough give to reduce the onset of fatigue and strain in feet, ankles, pelvis and back.

39" x 78" UPS Weight 68 lbs.
1 1/4" hole diameter

SCREW-DRIVE CURTAIN COMMANDER™

AIRSTREAM VENTILATION SYSTEMS Curtain Commander™ Screw Drive Automated Ventilation Curtain Controller by design is unsurpassed for durability and simplicity of operation.

- Reversible brake drives available in 15 and 60 RPM models • 3,000 lb. lift capacity (contact factory for restrictions).
- High strength zinc-aluminum alloy drive-block features drive bearing properties superior to bronze and plastic materials.
- Engineered aero-space plastic guides allow for drive-block stability and maintenance-free operation. (Does not require lubrication).
- Hightech hytral power coupler rated to protect gear-drive assembly with maximum flex alignment-minimal wear.
- Isolated primary and secondary actuation switches allow for back-up protection.
- Adjustment rods by design allow for ease of adjustment and simplicity of wiring. (All wiring at drive end).
- New one- and two-piece fiberglass composite cover assemblies for lifetime service.

NVI CONTROL Precisely adjustable in all ways. Lets you adjust both the run time and the pause time. It even lets you choose a different rate for opening and closing. Adjustable dead band and heater interlock make it the most accurate digital control on the market for natural ventilation... and it's standard equipment with the Curtain Commander™.

LATCH-OUT ASSEMBLY Fully adjustable latch-out assembly available on all Curtain Commander™ machines. (Can be retro-fitted to selected models). Allows for total flexibility in tunnel-ventilated buildings. Shuts off fans when curtain reaches desired opening.

SUNNE

TF-115 THERMO STAT

AIRSTREAM VENTILATION SYSTEMS

A Division of **GSI**

AAA GLASS-PAC FIBERGLASS VENTILATION FANS

Streamlined Fiberglass Fan Housing

- Plastic Shutter
- Solid One-Piece Fiberglass Propellers
- Heavy Duty Motors
- All Aluminum Motor Unit
- Stainless Steel Hardware
- Vinyl-Coated Steel Front Guard

AAA NEVER-RUST AIR FOIL SHUTTERS
NO RUST, NO CORROSION

AVAILABLE IN BACK-DRAFT MODEL

TANDEM PRODUCTS, INC. LIVESTOCK EQUIPMENT

Tenderfoot/NS

For Small Animals Up To 100 Lbs

Tenderfoot/NS (Nursery) is specifically designed for use in standard nurseries and will accommodate pigs up to 100 lbs. Tenderfoot/NS is also used for many other small animal applications such as zoos, dog kennels, etc.

A Softer Warmer Bedding-Type Environment
When installed in the outer edges or creep area of a farrowing crate, Tenderfoot/NS will greet your newborn piglets with a soft warm bedding type environment. Those painful and costly bruises, abrasions and other discomforting problems are greatly reduced! Tenderfoot/NS 9 gauge expanded metal has hose openings that measure 1/4" x 1/4".

BOSS HOG FLOORING FOR ALL CONFINEMENT NEEDS

Woven Wire "New" Size 3/8"x3" - 5/16" Wire In Stock
3/8"x2 - 5/16" Wire 3/8"x1 1/2" - 243" Wire

ENERGY EFFICIENT ENCLOSED MOTORS

- Heavy-duty totally enclosed motors with sealed ball bearings are designed for continuous work load.
- Available in two-speed.
- Built-in thermal overload for low line-voltage protection on all single phase motors.

ALUMINUM SHUTTERS:

- All Aluminum Construction
- Counter Balanced Blades
- Nylon Bearing
- Stainless Steel Hinge Pins
- Low Air Resistance *
- Reduces Sticking in Dusty and Moist Conditions *

SEE US FOR YOUR REMODELING NEEDS

Compare the difference!

SCHAFFER Barn Kooler

The only patented air circulation fan on the market!

Because of its design, it provides more air movement and therefore more cooling effect than any other circulation fan.

U.S. Pat #4,819,183

AIRSTREAM VENTILATION CONTROLS

A.T. NEWELL

MODEL AC506 STANDARD...

...operates curtains on cable system by winching cable around a grooved drum controlled by a thermostat and time clock.

The model AC506S version uses a sprocket and chain drive (instead of drum) that turns a pipe running the length of the building to pull the curtain or door drop cords directly around the pipe eliminating need for cable (operates same as AC506).

DOSATRON LIQUID DISPENSER

Accurately Meter...
Antibiotics • Coccidiostats
• Drugs • Disinfectants • Sulfas
• Vaccines • Wormers • Vitamins
• Fertilizers • Chemical Additives...
into livestock and poultry drinking water or into irrigating systems.

Adjustable ratios: 1:100, 1:128, 1:200
Dosatron 7 GPM Technical Specifications:
Adjustable Ratios: 1:100, 1:128, 1:200
Minimum Flow: 13 GPH
Maximum Flow: 400 GPH
Min. Oper. Pressure: 7 PSI
Max. Oper. Pressure: 72 PSI
Connections: 1/2" NPT
Dimensions: Height 11" Width 8" Weight: 3.5 lbs.

7 GPM MODEL

BURN-EASY Incinerators

The quick, easy way dispose of dead animals. Very little odor, minimum smoke and residue.

- 100#, 300#, 500# and 600# models
- Leaves 1 gallon of ash per 100#
- Burns 50# of flesh per hour
- Large units have 30" end loading door
- Low profile, easy-to-load
- Oil firing unit has 1-year guarantee
- Optional 14" clean-out door

AIRSTREAM VENTILATION SYSTEMS

A Division of **GSI**

CEILING INLETS

Each unit provides 1.2 square feet of intake area and is designed to operate under negative pressure. Inlets are constructed of fiberglass composite and Styrofoam. Units measure 16.5" square and mount directly into the ceiling and project into the attic. An insulation-stop is provided. Stainless steel counter weights and a manual lock adjustment make it unsurpassed in performance.

Counter Weight

AIRSTREAM VENTILATION SYSTEMS

AAA MAKI-BRUTE™ SLANT-WALL BELT DRIVE FANS

- Never rust • Never need painting • Lifetime guaranteed fiberglass composite props
- Airfoil shape • Perfect balance, never rust or corrode • Choose 36", 42" or 48" size
- Streamlined aluminum motor mounts • Strong, rust proof • Optional Discharge Cone of Lifetime-Guaranteed Fiberglass Composite • The right design to boost fan performance 10-15% and the right material to last without maintenance • Energy efficient motors • Save operating costs year after year
- Slant Wall Housing of Lifetime-Guaranteed Fiberglass Composite • The right design for wind and weather and the right material for long life

THE LAST FAN YOU EVER NEED TO BUY
Unique construction, more features than any, better than steel yet costs no more • Lifetime-Guaranteed Discharge Cones (optional)
• Aluminum Motor Mounts • Automatic Belt Tightener • Cast Solid Belt Pulleys • Larger, Stronger 1" Drive Shafts • Stronger Cast Iron Pillow Blocks for Proper Shaft Alignment • Longer Lasting One-Inch Quality Bearings • Vinyl Clad Metal Guards

FULL COMPLEMENT OF OPTIONAL ACCESSORIES
• Motor-Driven or Back Draft Shutters with Quick Release Mounts
• Motor Control • Computers For Automatic Operation
Avail. In 36" & 48"

TRUCKLOAD SALE.. FANS.. 36" & 48"

ACME Breeze Master

BELT DRIVE OR DIRECT DRIVE PANEL FANS FOR AGRICULTURE

FAN STRUCTURE

- All galvanized frame and orifice - corrosion resistant long lasting
- Premounted in particle board box - easy handling and fast installation with wire screens on both sides
- Vertical support - maintains proper alignment
- Quiet operation - no disturbance during operation
- Direct Drive - no drive losses, no belts to slip
- Optional Discharge Diffuser Cone - Increases performance of fan without additional HP

PROPELLER
All galvanized blades riveted to matching heavy gauge galvanized spider. High performance camber twist propeller, stabilizes air flow through lower speeds.

MOTOR
High efficiency "C" face mounted motor includes thermal overload protection, gasketed wiring and capacitor covers. Delivers high CFM at normal speed with capability of operating at lower speeds without overheating. Speed may be controlled with PB 100 Series speed controls.

LIFETIME GUARANTEED FIBERGLASS COMPOSITE HOUSINGS!

QUALITY GSI BINS

We Assemble, Deliver & Set-Up Bins On Your Farm

Full Line Of Parts In Stock For Your Poultry And Hog Needs

Hours: M-F 7:00-5:00; Sat. 7:30-11:30

Swine & Poultry Systems Specialists

FARMER BOY AG.

410 E LINCOLN AVE. (RT 422) MYERSTOWN, PA 17067 INC

PH. 717-866-7565

Check Our Warehouse Prices

WE SHIP UPS

MasterCard VISA

See JAY, PAUL OR STEVE For Your Parts And Equipment Needs