

FARMER BOY AG MC.



Your Complete Poultry & Swine Building & Equipment Center

GESTATIONAL STALLS

Slope-Front- allows for easier movement by increasing aisle

SPECIFICATIONS

Standard Legs: 7/8" round x 1/4" flat OR 1" round x 3/8"

Features

horizontal bars.

Our Own Hog Confinement Equipment Now With Baked-on Powder Coated Finish At Discounted Factory Direct Prices

FENCING Vertical




All Farmer Boy fencing is available in black iron, hotdipped galvanized or painted. Fasteners available from Farmer Boy: thunderstuds, Tbolts, etc.

SPECIFICATIONS

*Solid rod or Schedule 40 pipe 3/8" rods 2 1/2" on center 1/2" rods 3 1/2" on center 1/2" rods 4 1/2" on center 26" high 30" high Grower 32" high Finisher . 1/2" rods 4 1/2" or 6" on center 40" high Breeding

Height is measured installed from floor to top of fencing Posts Available: 1-way, 2-way, 3-way, or 4-way 1" Solid or 1" Schedule 40 pipe. Available with step for operator convenience

HORIZONTAL OPTIONS



For the gate to open this style pin needs to be lifted ONLY one-third of the distance resulting in convenience for the operator and a decrease in the amount of

Leg Styles Standard stainless steel welded on Bolt-on This leg adds stability and is easily fastened to floor. Can be sold separately for easy replacement 1/4 or 3/6*

SPECIFICATIONS

SPECIFICATIONS
3/8" rods in center
Angle 1/8"x1"x1"
3/15" Vertical flats
1/2" rods in center
1/2" rods in center
3/4" rods on bot
1/2" rods in center
3/4" rods on bot
1/2" rods in center
3/4" rods on bot
4/4" rods on bot
4/4" verboat flats
Height is measured installed from floor to top of fenong

HORIZONTAL

space available for operator.

Vertical Rods: 1/2"

flat OR stainless steel

Frame Construction: 7/8" steel rod

Feed Tube: 2" schedule 40 pipe

FEATURES: Drop-Back- allows for easier movement by increasing space available for operator to perform pregnancy tests and medication

VERTICAL

Drop-Back- designed for easy

operator access for pregnancy

testing and administering

medications - through rear

Straight-Front- allows more room for sow mobility *Also available in slope-front

SPECIFICATIONS Frame Construction, 3/16" or 1 1/2" angle on bottom 1/8" x 1 1/2" angle on top eed Tube 2" schedule 40 pipe fonzontal Rods 1/2"

Available Legs. 1/4", 3/8", or 1/4" stainless steel

This design allows for easy fastening to concrete slats (see picture)


FARROWING CRATES

FEATURES: European style; Bowed bar adjustable side rails; Anti-crush rump guard on rear door; Large, efficient, stainless steel feeder has no sharp edges.

MODEL 60

SPECIFICATIONS: 7/8" solio steel construction. **OPTIONS:**

- · Available with finger bars
- Black iron, hot-dipped
- galvanized, or painted Water set-ups stainless steel or hot-dipped galvanized pipe
- Creep Sets stainless, hotdipped galvanized, or PVC
- Crate stands hot-dipped galvanized, painted, or black iron



Pig saver bar OR finger bars Black iron, hot-dipped galvanized,

Rump guard on rear door
Creep sets stainless steel hotdipped galvanized or PVC
Crate stands hot-dipped galvanized,

painted, or black iron Water set ups stainless steel or hot-dipped galvanized pipe

SWING SIDE

MODEL 70

FEATURES:

Standard 3 position adjustment for sow comfort, Swing-side easily adjusts to size of sow, Standard - bowed bar sides, No cylinders!, No sharp edges!, Front & Rear Gates swing both right and left, Large, efficient stainless steel and left, Carge, efficient stanless steep feeder has no sharp edgest, Pig-saver bar decreases death rate of piglets, Rubber bumper guards reduce noise and injuryl, Feeder raised off of floor to increase ventilation for sow comfort

SPECIFICATIONS: 1" schedule 40 pipe construction, Bottom 6" on legs are 1" solid rod

MiraFount BEEF/ BEEF/ ENERGY FREE WATERERS DAIRY DAIRY THE PROVEN ENERGY FREE SYSTEM WIND STATES MODEL #3360 MODEL #3410 **MODEL #3310-S**

Hogs

2 lift up fels

9 123 116 Inii

E (TEN)

ENERGY EFFICIENT

ENCLOSED MOTORS

WELDED FINISHING FEEDER

OPTIONS:

- 304 Stainless Steel construction All welded construction
- Easily adjustable and multi-movement agitator gate All exposed edges are hemmed for safety
- Standard Single-Sided models available with 4, 5 and 6 holes, Standard Double-Sided models available with 8, 10 and 12 feed holes 7 hole and 14 hole sizes avail-

4-Hole Double-Sided Finishing Feeder

able (special order only)




SUNNE THERMOSTAT

Thermostat Has A Sealed Molded Plastic Case With All Exposed Metal Parts Of Stainless Steel, Intended For Applications That Need A Rugged Weatherproof Type Control Suitable For Either Heating Control Or Cooling Control.

Schaefer Barn Kooler®

The Barn Kooler® System incorporates circulated.



ENERGY EFFICIENCY

AND LONGER LIFE

a series of fans and controls into an integrated system that is used for both high velocity air cirulation for cooling during the Summer and gentle, draftfree air movement during the Winter months. By utilizing thermostically controlled speed modulators, the speed of the circulating air is constantly adjusted to the temperature. As the temperatures in the building rise and fall, so does the volume of air being

Sizes 20" - 24" - 36"

Use Flourescent Lighting For Energy Savings

Light Buibs

U-TUBE LAMP & SUPPLIES

"...the biggest advantage of these lamps is the conomic savings over the life of the bulb. Once the nitial investment is paid back, which will be done in eas then six months, the increased electrical conomy make such bulbs the most logical way to @ht..." MICHAEL J Darre - PHD Animal Science University of Conni

It's Time To Change Your Bulb® PAR HEAT LAMP




30% Wattage Reduction, Savings Of

Over \$37 Per Lamp Over The Life Of The Lamp = Energy Saving

Long Life Standard 125 to 250

SAVINGS OVER LIFE SLS 23 WATT EARTH LIGHT Barth Light Collection lamps pay for themselves many arms over by providing significant savings on energy, maintenance and replace mosts. Compared to extinsty incan descent lamps Barth Light Collec-tion lamps always to 76 percent en-country. The SL523, for sample will see \$675 over the 16 of each lamp. What's more, these energy savinass are commonated by sav-savinass are commonated by savvon longs last up 10 to 13 longer than ordi



Watt Available SEE STEVE, TODD OR JAY FOR YOUR PARTS AND EQUIPMENT NEEDS



Electricity Water Incursion Smoke

Windows & Doors

CONDITIONS MONITORED

Humidity

NEW

Sensaphone 1100

Advanced Desktop Monitoring System

Environmental/Process monitoring

over telephone lines with full

programming capabilities

Variable power failure recognition and listen in time with alarm disable security code access remote sensing and other programming features.

the important environment onditions to protect compl quipment and processes

Helps you detect problems before they turn into disasters

ow you can protect your equip-sent and processes even when yo

Sound


LP TO 4 DIAL OUT NUMBERS











Low Air Resistance Reduces Sticking In Dusty and Moist Conditions



Swine & Poultry Systems Specialists

410 E LINCOLN AVE

PH. 717-866-7565



Hours: M-F 7:00-5:00;

Sat. 7:30-11:30

Check Our

Warehouse **Prices**





