

# PARMER BOY AGINC.

Your Complete Poultry & Swine Building & Equipment Center



A Division of **GSI** 





Each unit provides 1.2 square feet of intake area and is designed to operate under negative pressure. Inlets are constructed of fiberglass composite and Sytrofoam. Units

THE PURAFIRE

Our name says it all

The PuraFire heater provides a consistent, clean-burning and fuel-efficient source of warmth for all types of poultry and swine houses. With near 100% efficiency (CO emissions of 5 parts per million), the thermostatically operated PuraFire uses less energy to yield greater BTUs for your money. Choose from two PuraFire models: the C80M - variable output

(40,000 or 80,000 BTUH) and the C225-225,000 BTUH unit Each is LP or natural gas compatible


an be mounted inside or outside your confine-

measure 16.5" square and mount directly into the ceiling and project into the attic. An insulation-stop is provided. Stainless steel counter weights and a manual lock adjustment make it unsurpassed in performance.

ment house.







Hi-Lo Livestock Production Ther-


mometers. This quality thermometer is one of the most economical, accurate instruments on the market. A must for anyone in livestock production or greenhouse operations wherever temperature control is important. It shows at a glance the lowest and highest temperatures over a period of time plus the present temperature. Available in centigrade/ fahrenheit or fahrenheit only. It is easy to use with a push button reset.



Tamy Hog Cream is a waterless hand cleaner that removes those awful farm odors, fish odors, onion odors, grease, and grime from hands. Leaves hands smelling good, feeling fresh and clean. Just simply apply a small amount to hands and rub well until it dissolves and suspends the grease and grime, rinse with water and rub clean. Comes in a pint size squeeze bottle. Shampoo is also







 High insulation value one inch (1") polystyrene core. • Corrosconfree construction consists of rugged fiberglass composite laminate and UV sublized PVC trim channel. • Exclusive Recuble PVC hinge allows for ease of installations and alignment. Flexible PVC closure allows for building construction variables. • Exclusive PVC. metically adjusts to temperature varia-nt closure alignment. • Rod and clamp expension connector aut tions and ensures consistent close ory pack feature unique cord adjuster for precise closure arnt. •AIRSTREAM VENTILATION SYSTEMS Adjust-A-Baffle<sup>16</sup> Systems can be installed to allow for vertical or horizontal inlet openings. • Adjust-A-Baffle<sup>16</sup> panels available in wide range of standard and custem width dimensions; standard widths include 5", 12", 16", 18", 20" and 24". Contact factory for custom width

## THERM-ALARM III

- Hermetically **Sealed Contacts**
- · Easily Adjusted Set Hands
- · Durable, Accurate, Reliable

ADJUST-A-BAFFLE" SYSTEM

- Quick Response To Temp. Changes
- · Fully Guaranteed

New **Concept Alarm Thermometer** 



The Nitrogen level of the pit waste will be enhanced by 300% with

PIT-BOSS™

Pit Additive To Reduce Odor And Pit Solids



Galvanized & PVC



PVC **Ball Valve** 

WATER FILTER



- Hours: M-F 7:00-5:00;

SHIP

UPS

Sat. 7:30-11:30

Check Our

Warehouse

Prices

VISA

PLUMBING SUPPLIES



## Farmer Boy Ag Stabling

Buy Direct From The Mfg. & Save For Your Existing Or New **Equipment Needs.** 

Model 70 Swing-Side

- Pig-saver bar OR finger bars
  Black iron, hot-dipped galvanized,
- or painted

  Rump guard on rear door

  Creep sets: stainless steel, hot-
- dipped galvanized or PVC Crate stands hot-dipped galvanized, painted, or black iron Water set-ups: stainless steel or hot-dipped galvanized pipe

FEATURES:

Standard- 3 position adjustment for sow comfort; Swing-side easily adjusts to size of sow; Standard - bowed-bar sides; No cylinders!; No sharp edges!; Front & Rear Gates swing both right and left!; Large, efficient stainless steel feeder has no sharp edges!; Pig-saver bar decreases death rate of piglets; Rubber bumper guards reduce noise and injuryl: Feeder raised off of floor to

SPECIFICATIONS: 1" schedule 40 pipe construction, Bottom 6" on legs are 1" solid rod.

### HORIZONTAL

**OPTIONS:** Pin Styles

For the gate to open, this style pin needs to be lifted ONLY one-third of the distance resulting in convenience for the operator and a decrease in the amount of

pins lost! Leg Styles

Standard: stainless steel welded on Bolt-on: This leg adds stability and is easlly fastened to floor. Can be sold separately for easy replacement. 1/4" or 3/8"

**DUST/MIST** 

Respirator

WHY TAKE CHANCES: Help protect yourself against breathing in harmful odors and feed and grain dust found in hog facilities. The dust/

mist respirator features a nose cushion and a contoured nose clip for a more reliable seal for greater portection. It

includes a collapse-resistant shell that

is reliable in hot humid conditions. The

dust/mist respirator is NIOSH/NSHA

approved for dust and mists. The mask

is a soft lightweight construction and

will easily fit around eye glasses. Dou-

ble strap ensures better fit for more pro-

		SPECIFICATIONS		
		3/8" rade in center	m Č	28" high
		. Angle 1/8"x1"x1"		
		3/16" Vertical flats		
•	٠.	, 1/2" rads in center3/4" rads on bottom	m	32° high
		, 1/2° rods in center . 3/4° rods on bottom	m	32° high
		, 1/2° rods in center 3/4° rods on bottom		44" high
		Angle 3/16" x 1 1/2" x 1 1/2"		•
		1/4" Vertical flats		
		Height is measured installed from floor to top of fencing		

### *Sensaphone*\* 1100 Advanced Desktop Monitoring System

mini/Process monitoring

over telephone lines with full programming capabilities

Finisher



**ALERT** 




4-Hole Double-Sided Finishing Feeder

- All exposed edges are harmond for safety. Standard Single-Sided models available with 4, 5 and 6 heles; Standard Double-Sided

Full Line Of Parts in Stock For Your Poultry And Hog Needs

24



410 E LINCOLN AVE

2-3

PH. 717-866-7565 800-845-3374 Ask for Steve, Todd or Jay for your Parts & Equipment Needs





FAN SIZE	FAN MODEL	MOTOR H P	PROP RPM	0	05
8"	POPE-8	1/15	3400	585	570
10"	POPF-10	1/6	3400	1155	1140

