
Deutz DX160, 4x4, cab, less than 200hr on complete overhaul on engine and trans., excellent, OBO \$20,500 17/762-3403, 301/739-6632 717/762-8590, No Sunday

2) 950 Badger Wagons Tandems and Roofs. **Excellent Condition** (201) 764-4681



Martin Tractor

866 Greenspring Rd. Newville, PA 17241

Used Tractors: G 1000 Vista \$4,500; White 2-150 \$7,500; Oliver 1850 3 Spd. \$6,000; IH Super H w/live hyd. \$2,300; JD 530 w/3pt. & front wts. \$4,500; JD 4040, like new, 221 org. hrs.

Used Tractor Parts Most Makes and Models

New rear Z tractor rims X 18x38 and X other Have Large Selection
Recent Arrivals: JD 70 dsl.; JD 2040;
JD 2020; Case 1175; MM G1000, BF Avery A, Oliver 550, JD 3010, Oliver 1600, IH BN; Case 630; Case 970; IH C: IH 460; IH 756; AC D17; Ford 4500; IH SM; IH SMTA; Oliver 550

> Call (717) 776-7542 or 6057 (717) 776-7327 Fax


for detailed information **MON-FRI 8-5**

SAT 8-12

No Sunday Calls

Will Ship UPS

No Out-Of-State Personal Checks



Oliver 1650, Gas, 4,300 One Owner Hours, 12 Speed, Nice Midwestern Unit

\$4,200

Also Available: Oliver 1855, 4x4 w/Cab

\$6,500

Oliver 1800, Diesel, WFE

\$2,200

Financing & Trucking Available

410-833-9091

FROM HARDPAN SHATTERING TO RESIDUE COVERED FINISHED SEEDBEDS... SUNFLOWER EXCEEDS YOUR TILLAGE NEEDS

"Boiling, uplifting action in the soil allows water to enter and be retained in subsoil, minimizing runoff. Yield increases up to 10 bu. more corn per acre." Lancaster Co. farmer.

Sunflower Subsoiler Coulter Rippers In Stock At Binkley & Hurst Bros., Inc.



COULTER RIPPERS



These shanks are equipped with special hardened replaceable wear bushings in every pivot point and contains grease zerks in required locations. The shank features a maximum point load of 5100# offers a tripping height capable of clearing obstructions and will automatically re-set itself after tripping. Each shank is equipped with a replaceable point and will accommodate a shatter wing for additional fracturing of the soil. It's produced from 1.1.4" x 4" his strength material and features an on edge design. maximum point load of 5100#



The optional shatter wing can be installed on each shank it ditional fracturing of additional tracturing of the soil is desired. It features replaceable plain or hardlaced punts. This attachment is available for either 4010,4110 Coulter Rippers or 4311 Disc Rippers.

3 Pt. Models Available Ask For A Demonstration Today!

YOU DESERVE TH **INDUSTRY'S BEST. FOR LESS!**

SUNFLOWER

FIELD CULTIVATOR



The industry's finest high-residue field cultivator featuring the structural integrity today's operators demand.

We challenge you to compare. Sunflower quality at a lower price. Ask for details.

SUNFLOWER RIPPERS

- * VERSATILE
- * ADAPTABLE
- **★ TOUGH**
- **★ PROVEN Check Out These Features:**
- ✓ 10'-18' Frame
- ✓ 3-9 Shanks On Infinite Spacing From 15"
- 36" Under-Frame Clearance
- ✓ Heavy Duty Trip Mechanism Allows Shanks To Trip **Back 36***
- ✓ 10' & 14' Frames In Stock
- ✓ We Will Install Your Choice Of Number Or Shanks To Match Your Tractor Horsepower
- ✓ 5100 ib. Max Point Pressure ✓ 2" Slip-In Spindles On 2 Or
- 4 Wheels ✓ 16" Upward Tripping Clearance On Auto Reset
- Shanks ✓ GREAT PRICE VALUE!!







8'9" to 18'9" Widths Available!

CHECK OUT THIS **SUPERIOR NEW** PRODUCT FROM SUNFLOWER!

New extended frame length for better trash

Auto-reset trip · Heavy-duty 4"x6"x% "

mainframe construction. · Hydraulically controlled coulter gangs (optional) can be adjusted on the go or raised completely in clean soils.

Four inch twisted shovels provide maximum residue incorporation. Optional 2" reversible shovels team with hydraulically-adjustable coulters to give maximum residue cover while "perforating" plow pan to encourage water retention. TAKE A

SUNFLOWER, SUPERIORITY -PROVIDES THE QUALITY YOU DEMAND

WHY BUY A SUNFLOWER DISC HARROW?

The Reasons Are Obvious!

Sizes From 10'-15' And 18'-32' Folding Check Out The Rest -

Then Buy The Best! SUNFLOWER

WING GAUGE WHEELS

BLADES: 1/4 "x22" or 1/4 "x24" On 8.5" Sp 3 Sided Siede Prevente Erosion & Eliminating A Continuous Furrow

DOUBLE OFFSET DESIGN Provides Maximu Leveling Without A Middle Suster Or Center Tooti ddie Buster Or Center Tooth

Your Cheice Of RIGID or C-FLEX BEARING STANDARDS.

TRANSPORT WIDTH On Ning Units Up To 24'2' Working Width Is A SAFE 12'4" Transport.

LOOK,5

S YEAR WARRANTY On Triple Lip Secied Trunnian Mounted.

HEAVIEST AXLE SHAFTS In The Industry - 1% " Die. Genge Are Hydraulicelly Torqued To 1400 Lise. & Spring-Leaded To Elizabeta Leasening Many And

SELF-LEVELING HITCH Maintains s Level Setting Regardless Of Desired Depth Or Tilisge Applic

Sizes Available: 10', 12', 13' and Hydraulic Fold Model 18'-21' and 24'



Operation Now!

CALL BINKLEY & HURST FOR A QUICK DELIVERY!

133 Rothsville Station Rd. P.O. Box 0395, Litita PA 17543-0395 Located 1/2 Mile North of Rothsville (717) 626-4705 1-800-487-2978



TRANSPORT WIDTH

port width on 18'-21'-24' units are only 12'4" barely the width of your dual wheels, leaving plenty of room for traffic to pass. Transport height is within legal limits.

