

SUPPLIES AND REPAIRS.

In connection with the manufacture of this line of Combination Swings I handle supplies of every sort for repairs, and would call your particular attention to the clever device used for rope adjustments and manufactured exclusively by me. It is made of steel and is used to connect the suspending rope to the screw-eye or hook in the ceiling and is so adjustable as to very handily lengthen or shorten the ropes to the fraction of an inch.

DIRECTIONS FOR HANGING.

Screw four screw eyes into the ceiling at distances apart to correspond to the points at which the ropes fasten to frame of swing. Then simply snap ends of ropes into the screw eyes and adjust to any height desired. The back part of all swings should hang from 1 1/2 to 2 in. lower than the front part to insure the greatest comfort and ease of motion.

LIST OF PRICES.

No. 1—Swing.....	With Ropes, Snaps, Screw Eyes and Adjustments.....	\$ 8.62
“	“ “ “ “ no “	8.03
“	With Steel Wheels and Axles complete for Roller Chair.....	21.50
“	Complete on No. 1 Lawn Frame.....	13.50
No. 2— “	Complete, with Ropes, Snaps, Screw Eyes and Adjustments.....	5.62
“	“ “ “ “ no “	5.50
“	Complete on No. 1 Lawn Frame.....	10.88
No. 3— “	Prices same as No. 2.	
No. 5—Double Swing—for Porch—no Lawn Frame.....		15.00
No. 5—Double Swing—Porch or Lawn—with No. 2 Lawn Frame.....		21.00
Lawn Frames—No. 1 Angle Steel—Japaned.....		5.62
“ “ “ No. 2 “ heavy for No. 5 Swing.....		6.75

No. 1—Swing with Steel Wheels and Axles complete for Rolling Chair, wheels with rubber tires and ball bearings, prices quoted on application.

Plated cord 3cts. per foot. Adjustments per set of four 75cts. Snaps each 6cts. Screw eyes 4cts. Hook bolts with thumb nuts 12cts each. Extra slats for repairs, any length, 12cts. each. An additional price of 75cts. for each six inches in width of swing over 42 inches.

To Change No. 1 Swing to Hammock—Unscrew the thumb nuts at lock, take hold of the back of swing with the hands pull back until the swing comes into a straight position for a Hammock then un-snap the front ropes and snap front ropes into the small iron that is riveted fast to joint where foot-rest and leg-rest are riveted together, and you have a hammock that cannot upset or collapse and that two persons can lie on. It has the exact conformation of a person when they are lying on their back.

To Change No. 1 Swing to Crib Cradle or Play-house—Take out the small hook bolt in leg-rest, unhook the two flat irons that hold up foot-rest to arm-rest, shift the foot-rest up and rest it on your knees, take hold of iron where front rope snaps into them and push them apart, push the foot and leg-rest with knees past the rivets in arm rail while arm rails are apart and then take the two flat irons that hold up foot-rest and hook the slotted hole over the rivet on back of swing, tighten up lock nuts and insert the two hook bolts, that were taken out of the leg-rest, tighten up thumb nuts on hook bolts, and you have the most complete crib cradle and play-house in the world. Positively no danger of upsetting, collapsing or coming apart in any way.

It is well to oil all the joints in the swing with sewing machine oil before using. Thereby causing the swing to work nice and easy.

L. C. BULLOCK,

Sole Patentee and Manufacturer

MILESBURG, PA., U. S. A.

